

Material Safety Data Sheet

24 Hour Emergency Phone Numbers:

**Medical: 1-800-327-3874
1-513-558-5111**

**Transportation:
1-800-535-5053
1-352-323-3500**

.....
 •NOTE: National Response Center emergency numbers to be used only in
 •the event of chemical emergencies involving a spill, leak, fire, exposure or
 •accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this MSDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

Section 1 - Chemical Product / Company Information

This Material Safety Data Sheet is available in Canadian French and Hispanic American Spanish upon request.
 Esta hoja de datos de la seguridad de los materiales está disponible en francés canadiense y en español a su solicitud.
 Los Datos de Seguridad del Producto pueden obtenerse en Espanol si lo requiere.

Product Name: 33 Glazing - All Colors
Product UPC Number: 7079812019 7079812117 7079812120 7079812121 7079812122 7079812124 7079871090 7079871112 7079871151
Product Use/Class: Glazing
Manufacturer: DAP Inc.
 2400 Boston Street Suite 200
 Baltimore, MD 21224-4723
 888-327-8477 (non-emergency matters)

Revision Date: 07/27/2006
Supercedes: 07/19/1999
MSDS Number: 00010401001

Section 2 - Composition / Information On Ingredients

Chemical Name	CASRN	WT%	ACGIH TWA	ACGIH STEL	ACGIH CEIL	OSHA TWA	OSHA STEL	OSHA CEIL	Skin
Calcium carbonate	1317-65-3	60-100	10 MGM3	N.E.	N.E.	5 MGM3 (respirable fraction)	N.E.	N.E.	No
Soya oil	8001-22-7	3-7	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.	No
Parrafinic process oil	64742-65-0	1-5	N.E.	N.E.	N.E.	500 PPM	N.E.	N.E.	No
Non-Asbestiform Tremolite	14567-73-8	1-5	10 MGM3	N.E.	N.E.	5 MGM3	N.E.	N.E.	No
Talc, non-asbestiform	14807-96-6	1-5	2 MGM3	N.E.	N.E.	5 MGM3	N.E.	N.E.	No
Antigorite, non-asbestiform	12135-86-3	0.5-1.5	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.	No
Silica, crystalline	14808-60-7	0.1-1.0	0.05 MGM.	N.E.	N.E.	10/(%SiO ₂ + 2) MGM3	N.E.	N.E.	No
Anthophyllite, non-asbestiform	17068-78-9	0.1-1.0	0.1 FIBE.S/CM ₃	N.E.	N.E.	0.1 FIBERS/CM ₃	1.0 FIBERS/CM ₃	N.E.	No
Titanium dioxide	13463-67-7	0.1-1.0	10 MGM3	N.E.	N.E.	15 MGM3	N.E.	N.E.	No

Exposure Notes:

CASRN	Exposure Note
14807-96-6	The talc (CAS number 14807-96-6) within this product naturally contains a non-fibrous tremolite (CAS number 14567-73-8), non-fibrous serpentine (CAS number 12135-86-3), and non-fibrous anthophyllite (CAS number 17068-78-9). Refer to 29 CFR 1910.1000 Table Z 3 for the permissible exposure limits associated with non-fibrous talc and these naturally occurring incidental constituents.

Important: Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); these limits may vary between states.

Note: An employee's skin exposure to substances having a "YES" in the "SKIN" column in the table above shall be prevented or reduced to the extent necessary under the circumstances through the use of gloves, coveralls, goggles or other appropriate personal protective equipment, engineering controls or work practices

Section 3 - Hazards Identification

Emergency Overview: A colored paste product with a little or no odor. WARNING! May cause eye, skin, nose, throat and respiratory tract irritation. Harmful if swallowed or absorbed through the skin.

Refer to other MSDS sections for other detailed information.

Effects Of Overexposure - Eye Contact: May cause eye irritation.

Effects Of Overexposure - Skin Contact: Harmful if absorbed through the skin. May cause skin irritation.

Effects Of Overexposure - Inhalation: Harmful if inhaled. Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes). Dust from dry sanding may cause eye, skin, nose, throat and respiratory tract irritation.

Effects Of Overexposure - Ingestion: Harmful if swallowed.

Effects Of Overexposure - Chronic Hazards: Prolonged and repeated skin contact may cause irritation and possibly dermatitis. Repeated or prolonged exposure may cause respiratory system damage.

Primary Route(s) Of Entry: Skin Contact, Eye Contact

Medical Conditions which May be Aggravated by Exposure: None known.

Section 4 - First Aid Measures

First Aid - Eye Contact: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

First Aid - Skin Contact: Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical aid if symptoms persist. Remove and wash contaminated clothing.

First Aid - Inhalation: If inhaled, remove to fresh air. If breathing is difficult, leave the area to obtain fresh air. If continued breathing difficulty is experienced, get medical attention immediately.

First Aid - Ingestion: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

Note to Physician: None.

COMMENTS: Call Medical Emergency at 1-800-327-3874 if any irritation or complication arises from any of the above routes of entry.

Section 5 - Fire Fighting Measures

Flash Point, F: Greater than 200
Method: (Seta Closed Cup)

Lower Explosive Limit, %: Not Established
Upper Explosive Limit, %: Not Established

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam

Unusual Fire And Explosion Hazards: No special protective measures against fire required.

Special Firefighting Procedures: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Wear proper protective equipment as specified in Section 8. Use absorbent material or scrape up dried material and place in container.

Section 7 - Handling And Storage

Handling: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Use only with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing. Wash thoroughly after handling. Open all windows and doors or use other means to ensure cross-ventilation and fresh air entry during application and drying. Odor is not an adequate warning for hazardous conditions.

Storage: Close container after each use. Store away from caustics and oxidizers. Store containers away from excessive heat and freezing. Do not store at temperatures above 120 degrees F.

Section 8 - Exposure Controls / Personal Protection

Precautionary Measures: Please refer to other sections and subsections of this MSDS.

Engineering Controls: Good general ventilation should be sufficient to control airborne levels. Ensure adequate ventilation, especially in confined areas. Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator with an organic vapor cartridge or canister may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Skin Protection: Rubber gloves.

Eye Protection: Goggles or safety glasses with side shields.

Other protective equipment: Not required under normal use.

Hygienic Practices: Remove and wash contaminated clothing before re-use. Wash hands before breaks and at the end of workday.

Section 9 - Physical And Chemical Properties

Boiling Range:	Not Established	Vapor Density:	Heavier Than Air
Odor:	Little or None	Odor Threshold:	Not Established
Appearance:	Colored	Evaporation Rate:	Slower Than n-Butyl Acetate
Solubility in H2O:	Not Established	Specific Gravity:	2.214
Freeze Point:	Not Established	pH:	Between 7.0 and 12.0
Vapor Pressure:	Not Established	Viscosity:	Not Established
Physical State:	Paste		

When reported, vapor pressure of this product has been calculated theoretically based on its constituent makeup and has not been determined experimentally.

(See section 16 for abbreviation legend)

Section 10 - Stability And Reactivity

Conditions To Avoid: Excessive heat and freezing.

Incompatibility: Incompatible with strong bases and oxidizing agents.

Hazardous Decomposition Products: Normal decomposition products, i.e., CO_x, NO_x.

Hazardous Polymerization: Hazardous polymerization will not occur under normal conditions.

Stability: Stable under recommended storage conditions.

Section 11 - Toxicological Information

Product LD50: Not Established

Product LC50: Not Established

Carcinogenicity:

CAS No.	Chemical Name	ACGIH	OSHA	IARC	NTP	WT%
14808-60-7	Silica, crvstalline	Suspected human carcinogen.	Not Listed.	Human carcinogen.	Known carcinogen.	0.1-1.0
17068-78-9	Anthophyllite, non-asbestiform	Confirmed human carcinogen.	Cancer hazard.	Human carcinogen.	Known carcinogen.	0.1-1.0
13463-67-7	Titanium dioxide	Not Listed.	Not Listed.	Classification not possible from current data.	Not Listed.	0.1-1.0

Significant Data with Possible Relevance to Humans: None.

Section 12 - Ecological Information

Ecological Information: Ecological injuries are not known or expected under normal use.

Section 13 - Disposal Information

Disposal Information: Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

EPA Waste Code if Discarded (40 CFR Section 261): none

Section 14 - Transportation Information

DOT Proper Shipping Name:	Not Regulated.	Packing Group:	N.A.
DOT Technical Name:	N.A.	Hazard Subclass:	N.A.
DOT Hazard Class:	N.A.	DOT UN/NA Number:	N.A.

Note: The shipping information provided is applicable for domestic ground transport only. Different categorization may apply if shipped via other modes of transportation and/or to non-domestic destinations.

Section 15 - Regulatory Information

CERCLA - SARA Hazard Category:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Immediate Health Hazard, Chronic Health Hazard

SARA Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS Number	WT%
Anthophyllite, non-asbestiform	17068-78-9	0.1-1.0

Toxic Substances Control Act:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

U.S. State Regulations

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product:

None

Pennsylvania Right-to-Know:

The following non-hazardous ingredients are present in the product at greater than 3%:

None

California Proposition 65:

Warning: The following ingredients present in the product are known to the State of California to cause cancer:

Chemical Name	CAS Number	Definition	Date Listed	WT%
Silica, crystalline	14808-60-7	Carcinogenic	Listed: October 1, 1988	0.1-1.0
Anthophyllite, non-asbestiform	17068-78-9	Carcinogenic	Listed: February 27, 1987	0.1-1.0

Warning: The following ingredients present in the product are known to the State of California to cause birth defects or other reproductive harm:

None

Section 16 - Other Information

HMIS Ratings:

Health: 1

Flammability: 1

Reactivity: 0

Personal Protection: X

VOLATILE ORGANIC COMPOUNDS, GR/LTR: 10.7 LB/GAL: 0.1 WT%: 0.486

REASON FOR REVISION: Periodic Update

Legend:

N.A. – Not Applicable

ACGIH – American Conference of Governmental Industrial Hygienists

N.E. – Not Established

SARA – Superfund Amendments and Reauthorization Act of 1986

N.D. – Not Determined

NJRTK – New Jersey Right-to-Know Law

VOC – Volatile Organic Compound

OSHA – Occupational Safety and Health Administration

PEL – Permissible Exposure Limit

HMIS – Hazardous Materials Identification System

TLV – Threshold Limit Value

NTP – National Toxicology Program

STEL – Short Term Exposure Limit

CEIL – Ceiling Exposure Limit

LD50 – Lethal Dose 50

LC50 – Lethal Concentration 50

F – Degree Fahrenheit

C – Degree Celsius

MSDS – Material Safety Data Sheet

CASRN – The Chemical Abstracts Service Registry Number

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. **NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS.** Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.

<End of MSDS>