

MATERIAL SAFETY DATA SHEET (MSDS)

MSDS NUMBER 105624D

SECTION I

January, 2005

INDEPENDENT MARKETING ALLIANCE

Houston, TX 77055 USA

PRODUCT NAME: ProPower SPRAY STAINLESS STEEL CLEANER AND POLISH

Emergency Phone Number: 1-800-851-7145 Ext. 075 (24 HOURS)

D.O.T. DESCRIPTION: CONSUMER COMMODITY, ORM-D

PRODUCT HAZARD RATINGS (HMIS®): - Health = 2, Fire = 4, Reactivity = 0 Protective Equipment = 8
(Rating Legend: - 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal, * = Chronic Hazard)

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Chemical Names	CAS #	SARA SEC 313	ACGIH TLV-TWA/STEL	OSHA PEL-TWA/STEL	% By Wt.
Synthetic Isoparaffinic Hydrocarbon	(64742-47-8)	No	NE / NE	52 ppm* / NE	10-30
Mineral Spirits	(64742-48-9)	No	177 ppm* / NE	177 ppm* / NE	10-30
Acetone	(67-64-1)	No	500 ppm / 750 ppm	1000 ppm / NE	10-30
Methyl Acetate	(79-20-9)	No	200 ppm / 250 ppm	200 ppm / 250 ppm	1-10
Propane	(74-98-6)	No	1000 ppm / NE	1000 ppm / NE	10-30

Balance of ingredients are non-hazardous or below reportable levels.

* Potential significant contribution to the overall exposure of this chemical via the skin

** ExxonMobil recommendation

SECTION III - PHYSICAL CHARACTERISTICS

Boiling Point: NA Vapor Pressure (psig): 100 @ 130°F / 47 @ 70°F Specific Gravity - calculated (H₂O=1): 0.7475 ± 0.005 pH: NA Solubility/Water: Negligible
Vapor Density (AIR=1): ND Evaporation Rate (Ether=1): ND Appearance and Odor: clear, colorless aerosol spray with solvent/lemon odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: Product is to be labeled as flammable as described in 16 CFR 1500.3 and 1500.45. Flashpoint: <0°F (Propellant); ≥4°F (Concentrate) Flammable Limits - % Volume in Air (Propellant): LEL: 2.2 UEL: 9.5 Extinguishing Media: Carbon dioxide, water spray, foam, or dry chemical. Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up. Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers. Unusual Fire and Explosion Hazards: Fire fighters and others who may be exposed to the products of Combustion should be equipped with NIOSH-approved positive pressure self-contained breathing apparatus (SCBA) and full protection clothing. At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

SECTION V - REACTIVITY DATA

Stability: Stable Hazardous Polymerization: NA Incompatibility (Materials to Avoid): Oxidizing agents. Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, hydrocarbon vapors. Conditions to Avoid: Keep away from heat, sparks, and flames. Dropping of containers may cause bursting.

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry: Inhalation: Y Eyes: Y Skin: Y Ingestion: N

HAZARDS IDENTIFICATION: EYES: May cause severe irritation. SKIN: May cause mild irritation. INHALATION: Irritating to eyes, nose and respiratory tract. Can cause dizziness, headaches and incoordination. Nausea, vomiting and stomach upset can occur. Under misuse or intentional misuse, product may cause asphyxiation. INGESTION: Exposure by ingestion is unlikely since an aerosol, but if ingested, the following may occur: Possible aspiration hazard - may cause inflammation of the lungs. May be harmful if swallowed. AGGRAVATED MEDICAL CONDITIONS: May aggravate pre-existing skin conditions. CHRONIC EXPOSURE: May affect the Nervous system. Eyes. Skin. EMERGENCY AND FIRST AID PROCEDURES: EYES: Immediately flush with plenty of water for at least 15 minutes. Get prompt medical attention. SKIN: Immediately flush with plenty of water for at least 15 minutes. Get prompt medical attention. INHALATION: Remove to fresh air. If symptoms develop, seek immediate medical attention. If not breathing, give artificial respiration. INGESTION: In the unlikely event of swallowing: Call physician immediately. Do NOT induce vomiting unless directed by medical personnel. Rinse mouth with water and give another cupful to drink. Never give anything by mouth to an unconscious person.

CARCINOGENICITY:

ACGIH IARC NTP OSHA
Acetone A4 No No No

TOXICITY INFORMATION: Acetone: After prolonged or repeated exposure, development of cataracts has been reported in laboratory animals.

LD50 Oral (Rat): 9750 mg/kg / LD50 Dermal (Rabbit): 20,000 mg/kg / LC50 Inhalation (Rat): 16,000 ppm/4hr /

Methyl Acetate: LD50 Oral (Rat): >5000 mg/kg LD50 Dermal (Rabbit): >5000 mg/kg / LC50 Inhalation (Rat): >16,000 ppm/4 hr.

Methanol: Reported to cause birth defects in rats exposed to 20,000ppm LD50 Oral (Rat): 5600-13,000 mg/kg

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Releases or Spills: Remove all sources of ignition and ventilate area. Soak up spill with an inert absorbent and place into a designated disposal container. Consult local regulatory agency for proper disposition of material. Waste Disposal Method: Do not puncture or incinerate containers. When contents are depleted continue to Depress button until all gas is expelled. Dispose of container in accordance with local, state, and federal regulations. Disposal regulations may be different for each state and/or locality. Handling And Storing: Avoid breathing vapor. Keep away from heat, sparks and flame. Use with adequate ventilation. Do not puncture or incinerate containers. Do not expose to direct sunlight or store at temperatures above 120°F (48.9°C). Store as Level 3 Aerosol (NFPA 308). Other Precautions: Please read and follow the directions on the product label; they are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

SECTION VIII - EMPLOYEE PROTECTION

Respiratory Protection (Type): None required if good ventilation is maintained. If exposure exceed Occupational exposure limits (Sec. II), use a NIOSH approved respirator to prevent overexposure. Ventilation: General ventilation is adequate under normal conditions; mechanical ventilation is optional. Protective Gloves: Chemical resistant gloves are recommended - consult glove manufacturer to determine the proper type for a specific operation. Eye Protection: Safety glasses are recommended. Other Protective Clothing or Equipment: Wearing of impervious clothing to prevent skin contact is optional. Work/Hygiene Practices: Ensure strict sanitary conditions are conformed to when working around chemicals. Protective clothing and equipment should be in accordance with 29 CFR 1910.132 and CFR 1910.133.

SECTION IX - OTHER REGULATORY CONTROLS

FEDERAL: Toxic Substance Control Act (TSCA): Ingredients of this product are listed on the EPA/TSCA Inventory of Chemical Substances.

STATE RIGHT-TO-KNOW: Pennsylvania/New Jersey Right-To-Know (Chemical and CAS No.): White Mineral Oil (8042-47-5), Synthetic Isoparaffinic Hydrocarbon (64742-47-8), Mineral Spirits (64742-48-9), Acetone (67-64-1), Methyl Acetate (79-20-9), Propane (74-98-6). CANADA: Domestic Substances List: Ingredients of this product are listed.

SECTION X - TRANSPORTATION (D.O.T. CLASSIFICATION)

Proper Shipping Name: Consumer Commodity Hazard Class: ORM-D

NG: Negligible NA: Not Applicable NE: Not Established UN: Unavailable ND: Not Determined

While the information set forth herein is believed to be accurate as of the date hereof, the Company makes no warranty or guarantee, express or implied, and disclaims all liability arising out of the use of this information.

8-XMSDS841285