

THOMPSON & FORMBY INC. -- THOMPSON'S WATER SEAL WATERPROOFING -- 8030-00-555-2878

=====
Product Identification
=====

Product ID:THOMPSON'S WATER SEAL WATERPROOFING

MSDS Date:05/17/1990

FSC:8030

NIIN:00-555-2878

MSDS Number: BJYZB

=== Responsible Party ===

Company Name:THOMPSON & FORMBY INC.

Address:10136 MAGNOLIA DRIVE

City:OLIVE BRANCH

State:MS

ZIP:38654

Country:US

Info Phone Num:901-685-7555 OR 714-864-2310

Emergency Phone Num:901-685-7555 OR 714-864-2310

Preparer's Name:C. A. EISENHARD

CAGE:THOMP

= Contractor Identification =

Company Name:CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

Box:City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US

Phone:909-864-2310

CAGE:60777

Company Name:THOMPSON & FORMBY INC.

Address:10136 MAGNOLIA DRIVE

City:OLIVE BRANCH

State:MS

ZIP:38654

Country:US

Phone:901-685-7555 OR 714-864-2310

CAGE:THOMP

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC PETROLEUM DISTILLATE (MINERAL SPIRITS)

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 85%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

=====
Hazards Identification
=====

Health Hazards Acute and Chronic: EYE: CAN CAUSE IRRITATION, REDNESS, BLURRED VISION. SKIN: PROLONGED/REPEATED CONTACT CAN CAUSE MODERATE

IRRITATION, DEFATTING, DERMATITIS. BREATHING EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS AND EVEN ASPHYXIATION.

Effects of Overexposure: SWALLOWING: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAUSES CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

=====
First Aid Measures
=====

First Aid: SKIN: THOROUGHLY WASH EXPOSED AREA W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE. EYES: FLUSH W/LARGE AMOUNTS WATER, LIFTING UPPER/LOWER LIDS OCCASIONALLY. GET MEDICAL ATTN. SWALLOW: DO NOT INDUCE VOMIT. KEEP WARM & QUIET. GET MEDICAL ATTN. INHALE: REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING DIFFICULT/CPR IF STOPPED. KEEP WARM & QUIET. GET MEDICAL ATTN.

=====
Fire Fighting Measures
=====

Flash Point Method: SCC

Flash Point: 101F, 38C

Lower Limits: 1.0

Extinguishing Media: FOAM, CARBON DIOXIDE OR DRY CHEMICAL.

Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS WITH A

FULL FACE-PIECE OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN FIGHTING FIRES.

Unusual Fire/Explosion Hazard: VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR BE MOVED BY VENTILATION AND IGNITE BY IGNITION SOURCES AT DISTANT LOCATIONS.

===== Accidental Release Measures =====

Spill Release Procedures: ABSORB ON SAND, CLAY OR OTHER ABSORBENT MATERIAL. ELIMINATE IGNITION SOURCES.

===== Handling and Storage =====

Handling and Storage Precautions: KEEP CONTAINERS CLOSED. STORE/USE AWAY

FROM IGNITION SOURCES. GROUND CONTAINERS WHEN POURING. LIMIT FREE FALL TO A FEW INCHES-PREVENT STATIC SPARKS.

Other Precautions: USE ONLY WITH ADEQUATE VENTILATION. AVOID PROLONGED AND REPEATED BREATHING OF VAPOR OR CONTACT WITH SKIN. RESINS ACCUMULATIONS (SUCH AS SPRAY BOOTH CLEANING) MAY BE SPONTANEOUSLY IGNITED. IMMERSE ACCUMULATION IN WATER. KEEP FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: IF TLV IS EXCEEDED THEN USE A NIOSH/MSHA APPROVED RESPIRATOR.

Ventilation: USE WITH ADEQUATE VENTILATION TO PREVENT EXCEEDING TLV.

Protective Gloves: HYDROCARBON SOLUBLE RUBBER OR PLASTIC.

Eye Protection: SAFETY GLASSES OR GOGGLES RECOMMENDED.

Other Protective Equipment: NONE REQUIRED.

Work Hygienic Practices: AVOID SKIN CONTACT. WASH CONTAMINATED SKIN AND CLOTHING WITH SOAP AND WATER.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt: B.P. Text: 300 TO 430F

Vapor Pres: 2.0

Vapor Density: 4.9

Spec Gravity: .800

Evaporation Rate & Reference: 70.0 (ETHYL ETHER=1)

Appearance and Odor: COLORLESS LIQUID WITH PETROLEUM DISTILLATE ODOR.

Percent Volatiles by Volume: 85

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
OXYGEN AND STRONG OXIDIZERS.

Stability Condition to Avoid:KEEP AWAY FROM HEAT, SPARK, FLAMES AND OTHER SOURCES OF IGNITION.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:PLACE WASTE IN CLOSED CONTAINERS. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS GOVERNING COMBUSTION WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.